# SAFETY DATA SHEET

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

ÚÜUÖWÔVÁÞŒ ÒKKKG Í Í FÁKKKKÖÜŒÚÒÜÁT WŠVQÆÖŒÙSÒVÁÖT ŐÍ Ï I

### ŒĹÚŠÔŒŀQJÞÙkÁ¥¥¥ŐŒÙSÒVÁØŠŠ

# SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### Classification (EC 1272/2008)

Classification (1999/45/EEC)

Physical and Chemical HazardsNot classified.Human healthSkin Irrit. 2 - H315;Eye Irrit. 2 - H319;Skin Sens. 1 - H317EnvironmentNot classified.Xi;R36/38. R43.Katarana Katarana K

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## 2.2. Label elements

Contains

2-HYDROXYPROPYL METHACRYLATE

Label In Accordance With (EC) No. 1272/2008

	•	
Signal Word	Warning	
Hazard Statements		
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
Precautionary Statements	5	
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
		lenses, if present and easy to do. Continue rinsing.
	P313	Get medical advice/attention.
	P501	Dispose of contents/container to
Supplementary Precaution	nary Statements	
	P272	Contaminated work clothing should not be allowed out of the workplace.

	DMG574
P261	Avoid breathing vapour/spray.
P264	Wash contaminated skin thoroughly after handling.
P321	Specific treatment (see medical advice on this label).
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P332+313	If skin irritation occurs: Get medical advice/attention.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P337	If eye irritation persists:
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P363	Wash contaminated clothing before reuse.

# 2.3. Other hazards

None if used properly

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

# 3.2. Mixtures

1-ACETYL-2-PHENYLHYDRAZINE			< 1%
Classification (EC 1272/2008) Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317		Classification (67/548/EEC) Xn;R22. Xi;R36/37/38. R43.	
STOT SE 3 - H335	ATE		10-30%
CAS-No.: 27813-02-1	EC No.:		
Classification (EC 1272/2008) Eye Irrit. 2 - H319 Skin Sens. 1 - H317		Classification (67/548/EEC) Xi;R36. R43.	
CUMENE			< 1%
CAS-No.: 98-82-8	EC No.: 202-704-5		
Classification (EC 1272/2008) Flam. Liq. 3 - H226 STOT SE 3 - H335 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		Classification (67/548/EEC) R10 Xn;R65 Xi;R37 N;R51/53	
CUMENE HYDROPEROXIDE			< 1%
CAS-No.: 80-15-9	EC No.: 201-254-7		
Classification (EC 1272/2008) Org. Perox. E - H242 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 3 - H331 Skin Corr. 1B - H314 STOT SE 3 - H335 STOT RE 2 - H373 Aquatic Chronic 2 - H411		Classification (67/548/EEC) O;R7 T;R23 C;R34 Xn;R21/22,R48/20/22 N;R51/53	

# DMG574

POLYETHYLENE GLYCOL 200 DIMETHACRYLATE			
CAS-No.:	EC No.:		
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Eye Irrit. 2 - H319		Classification (67/548/EEC) Xi;R36/38.	
TITANIUM DIOXIDE RUTILE TR92			< 1%
CAS-No.: 13463-67-7	EC No.: 236-675-5		
Classification (EC 1272/2008)		Classification (67/548/EEC) Not classified.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

# SECTION 4: FIRST AID MEASURES

#### 4.1. Description of first aid measures

#### Inhalation

Move to fresh air. If symptoms persist, seek medical advice

### Ingestion

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting Seek medical advice

Skin contact

Rinse with running water and soap Seek medical advice

#### Eye contact

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if neccessary

#### 4.2. Most important symptoms and effects, both acute and delayed

#### Skin contact

May cause sensitization by skin contact

#### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1. Extinguishing media

#### Extinguishing media

Carbon dioxide, foam, powder Unsuitable extinguishing media Not known 5.2. Special hazards arising from the substance or mixture

# Hazardous combustion products

Oxides of carbon, oxides of nitrogen, irritating organic vapors Do not expose to direct heat

# 5.3. Advice for firefighters

#### Protective equipment for fire-fighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear

# SECTION 6: ACCIDENTAL RELEASE MEASURES

# 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Provide adequate ventilation.

#### 6.2. Environmental precautions

Prevent entry into drains. 6.3. Methods and material for containment and cleaning up

# DMG574

For small spills wipe up with a paper towel and place in container for disposal For large spills absorb onto inert absorbant material and place in sealed container for disposal. Dispose of contaminated material as waste according to section 13

# 6.4. Reference to other sections

See advice in section 8

## SECTION 7: HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

Use only in well ventilated areas Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation Do not eat, drink or smoke when using the product. Wash hands before work breaks and after finishing work. Good industrial hygiene practices should be observed **7.2. Conditions for safe storage, including any incompatibilities** 

Store in original comtainers at 8-21°C (46.4-69.8 °F) and do not return residual materials to containers as contamination may reduce shelf life of the bulk product

## 7.3. Specific end use(s)

Anaerobic Sealant

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

Name	STD	TWA	- 8 Hrs	STEL	- 15 Min	Notes
CUMENE	WEL	25 ppm(Sk)	125	50 ppm(Sk)	250	
			mg/m3(Sk)		mg/m3(Sk)	
TITANIUM DIOXIDE RUTILE TR92	WEL		10 mg/m3			

WEL = Workplace Exposure Limit.

## 8.2. Exposure controls

#### **Respiratory equipment**

Use only in well ventilated areas

#### Hand protection

Nitrile gloves are recommended. Chemical-resistant protective gloves (EN 374) Suitable materials for short-term contact or splashes (recommended: at least protection index2, corresponding to >30 minutes permeation time as per EN 374): nitrile rubber (NBR;>=0.4mm thickness) Suitable materials for longer, direct contact (recommendation: protection index 6, corresponding to >480 minutes permeation time as per EN 374): nitrile rubber (NBR;>=0.4mm thickness) This information is based on literature references and on information provided by the glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chenical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced. **Eye protection** 

Wear approved safety goggles.

#### Skin protection

Wear apron or protective clothing in case of splashes.

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

Appearance	Paste
Colour	Orange.
Odour	Mild.
Solubility	Slightly soluble in water.
Initial boiling point and boiling range	>150 C
Melting point (°C)	
No information available.	
Vapour density (air=1)	1, 15 g/cm3
Vapour pressure	6, 6700000 mbar
Evaporation rate	
No information available.	
pH-Value, Conc. Solution	
Not applicable.	
Viscosity	
No information available.	

Decomposition temperature (°C) No information available. Odour Threshold, Lower No information available. Odour Threshold, Upper No information available. Flash point > 100 C Auto Ignition Temperature (°C) No information available. Flammability Limit - Lower(%) No information available. Flammability Limit - Upper(%) No information available. **Partition Coefficient** (N-Octanol/Water) Not available. **Explosive properties** No information available. **Oxidising properties** Not available. 9.2. Other information

No data available / Not applicable

# SECTION 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity

Reacts with strong acids Reacts with strong oxidants

#### 10.2. Chemical stability

Stable under recommended storage conditions

#### 10.3. Possibility of hazardous reactions

See section reactivity

# 10.4. Conditions to avoid

Stable 10.5. Incompatible materials

Materials To AvoidNo further relevant information available10.6. Hazardous decomposition products

Irritating organic vapours

## SECTION 11: TOXICOLOGICAL INFORMATION

# 11.1. Information on toxicological effects

## Inhalation

Inhalation of vapours in high concentration may cause irritation of respiratory system

# Ingestion

This material is considered to have a low toxicity if swallowed

## Skin contact

May cause sensitization by skin contact **Eye contact** Irritating to eyes.

# SECTION 12: ECOLOGICAL INFORMATION

# Ecotoxicity

Do not empty into drains / surface water / ground water

# 12.1. Toxicity

No Information available

# 12.2. Persistence and degradability

No further relevant information available

## 12.3. Bioaccumulative potential

#### **Bioaccumulative potential**

No data available on bioaccumulation. **Partition coefficient** Not available.

## 12.4. Mobility in soil

Mobility: Cured adhesives are immobile

# 12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB substances.

## 12.6. Other adverse effects

Not available.

## SECTION 13: DISPOSAL CONSIDERATIONS

#### General information

Dispose of in accordance with local and national regulations

#### 13.1. Waste treatment methods

Dispose of in accordance with local and national regulations Contribution of this product to waste is very insignificant in comparision to article in which it is used After use, tubes, cartons and bottles containing residue product should be disposed of as chemically contaminated waste in a authorised legal land fill site or incinerated Disposal must be made according to official regulations

# Waste Class

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

# SECTION 14: TRANSPORT INFORMATION

# 14.1. UN number

- 14.2. UN proper shipping name
- 14.3. Transport hazard class(es)

# 14.4. Packing group

- 14.5. Environmental hazards
- 14.6. Special precautions for user

# 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

# SECTION 15: REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. **Health and Environmental Listings** 

VOC content <5% (1999/13/EC)

# 15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

# SECTION 16: OTHER INFORMATION

Risk Phrases In Full	
R34	Causes burns.
R10	Flammable.
R22	Harmful if swallowed.
R21/22	Harmful in contact with skin and if swallowed.
R48/20/22	Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.
R65	Harmful: may cause lung damage if swallowed.
R36/38	Irritating to eyes and skin.
R36/37/38	Irritating to eyes, respiratory system and skin.
R36	Irritating to eyes.
R37	Irritating to respiratory system.
R7	May cause fire.
R43	May cause sensitisation by skin contact.
NC	Not classified.
R23	Toxic by inhalation.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Hazard Statements In Full	
H319	Causes serious eye irritation.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H242	Heating may cause a fire.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs < <organs>&gt; through prolonged or repeated exposure.</organs>
H335	May cause respiratory irritation.
H331	Toxic if inhaled.
H411	Toxic to aquatic life with long lasting effects.