

Thank you for purchasing a Sealey product. Manufactured to a high standard this product will, if used according to these instructions and properly maintained, give you years of trouble free performance.



IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS AND CAUTIONS. USE THIS PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. PLEASE KEEP INSTRUCTIONS SAFE FOR FUTURE USE.

1. SAFETY INSTRUCTIONS

- ✓ Follow workshop Health & Safety rules, regulations and conditions when using a grease gun.
- ✓ Maintain the gun and adaptors in good condition and replace any damaged or worn parts. *Use genuine parts only. Unauthorised parts may be dangerous and will invalidate the warranty.*
- ✓ Wear approved safety gloves and eye protection.
- ✓ Keep gun and adaptors clean and in good working order for best and safest performance.
- ✓ Keep children and unauthorised persons away from the work area.
- x **DO NOT** use gun or adaptors for a task it is not designed to perform.
- ☐ **WARNING! DO NOT** use gun or adaptors if damaged or thought to be faulty. Contact your local service agent.
- ☐ **WARNING! DO NOT** point the grease nozzle at yourself or others.
- x **DO NOT** operate until the nozzle is firmly attached to the receiving grease fitting.
- x **DO NOT** drop, throw, or abuse, the gun and accessory's.
- x **DO NOT** operate gun if you are tired or under the influence of alcohol, drugs or intoxicating medication.
- ✓ When not in use, store in a safe, dry, childproof location.

☐ **WARNING! The warnings, cautions and instructions discussed in this instruction manual cannot cover all possible conditions and situations that may occur. It must be understood that common sense and caution are factors which cannot be built into this product, but must be applied by the operator.**

2. INTRODUCTION & SPECIFICATION

Kit consists of adaptors and extensions to make almost any lubricating job easy. For use with all leading brands of manual grease guns.



- | | |
|---|--|
| <p>1. Press-on 90°.
90° angle for inaccessible grease fittings.</p> <p>2. Straight Extension.
Use to lubricate grease fittings where obstructions will not permit the use of hydraulic coupler.</p> <p>3. 12" Hose Extension.
Provides flexibility to tools with rigid extensions.
Provides additional reach where needed.</p> <p>4. Slide-on 90° Coupler.
Locks onto fittings that conventional couplers cannot.</p> | <p>5. Rubber Tipped Nozzle.
Lubricates machinery utilising grease plugs.
Lubricates spindles and capped lube ports.</p> <p>6. Needle Nozzle.
Allows operator to contact flush-type or hard to reach hydraulic-type fittings.</p> <p>7. 360° Coupler.
For full swivel, 2" steel extension tube and locking sleeve.</p> |
|---|--|

NOTE: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. **IMPORTANT:** No liability is accepted for incorrect use of product. **WARRANTY:** Guarantee is 12 months from purchase date, proof of which will be required for any claim.

INFORMATION: For a copy of our latest catalogue and promotions call us on 01284 757525 and leave your full name and address, including postcode.